

## **Expert finishes for wood and metal**

Rustins Ltd, Waterloo Road, London NW2 7TX. Tel: +44 (0)20 8450 4666 www.rustins.co.uk

Arsh Build Tech, Unit No-2, Gali No-4, Chauhan Colony, Haryana-121003 | +91-9958502276 | www.arshbuildtech.com

## February 2018

## PRODUCT DATA SHEET

| Intended Use Cleaning new and previously treated decks and exterior woodwork.  Special Features Revives the original colour of the wood on faded decks  Preparation Remove the loose dirt, grease, mildew and mould using a stiff garden brush.  Shake well before use. Decking Cleaner can be applied with a watering can, by spray or brush. Leave for 10 mins. then the surface should be scrubbed with a stiff garden brush or broom. Rinse the with clean water using stiff brush, garden hose or power washer.  Coats One application is usually sufficient.  Drying Time  Preparation  Re-coating Time Application Temp. Ideally 15-25 °C.  Coverage About 20-24 sq. metres. per 4 Litres.  Maintenance N/A  Compatibility Suitable for use on all types of timber and varnished surfaces.  Settlement  SHAKE WELL BEFORE USE.  |                    |   |
|--|--------------------|---|
| Intended Use Cleaning new and previously treated decks and exterior woodwork.  Special Features Revives the original colour of the wood on faded decks  Preparation Remove the loose dirt, grease, mildew and mould using a stiff garden brush.  Shake well before use. Decking Cleaner can be applied with a watering can, by spray or brush. Leave for 10 mins. then the surface should be scrubbed with a stiff garden brush or broom. Rinse the with clean water using stiff brush, garden hose or power washer.  Coats One application is usually sufficient.  Drying Time Application Temp. Re-coating Time Application Temp. Ideally 15-25 °C. Coverage About 20-24 sq. metres. per 4 Litres.  Maintenance N/A  Compatibility Suitable for use on all types of timber and varnished surfaces.  Settlement SHAKE WELL BEFORE USE.  | Product            | Decking Cleaner   |
| Special Features Revives the original colour of the wood on faded decks  Preparation Remove the loose dirt, grease, mildew and mould using a stiff garden brush.  Shake well before use. Decking Cleaner can be applied with a watering can, by spray or brush. Leave for 10 mins. then the surface should be scrubbed with a stiff garden brush or broom. Rinse the with clean water using stiff brush, garden hose or power washer.  Coats One application is usually sufficient.  24 hours depending on temperature and humidity. Do not apply decking coatings to damp timbe as this will affect the adhesion of the coating.  Re-coating Time N/A  Application Temp. Ideally 15-25 °C.  Coverage About 20-24 sq. metres. per 4 Litres.  Maintenance N/A  Compatibility Suitable for use on all types of timber and varnished surfaces.  Settlement SHAKE WELL BEFORE USE.   | Туре               | Rustin's Decking Cleaner is based on a special blend of special chemical agents to remove dirt, algae, mildew and grease from decking surfaces.   |
| Preparation Remove the loose dirt, grease, mildew and mould using a stiff garden brush.  Shake well before use. Decking Cleaner can be applied with a watering can, by spray or brush. Leave for 10 mins. then the surface should be scrubbed with a stiff garden brush or broom. Rinse the with clean water using stiff brush, garden hose or power washer.  Coats One application is usually sufficient.  24 hours depending on temperature and humidity. Do not apply decking coatings to damp timbe as this will affect the adhesion of the coating.  Re-coating Time N/A  Application Temp. Ideally 15-25 °C.  Coverage About 20-24 sq. metres. per 4 Litres.  Maintenance N/A  Compatibility Suitable for use on all types of timber and varnished surfaces.  Settlement SHAKE WELL BEFORE USE.  | Intended Use       | Cleaning new and previously treated decks and exterior woodwork.  |
| Application  Application  Coats  One application is usually sufficient.  Drying Time  Re-coating Time  Application Temp.  Application Temp.  Coverage  About 20-24 sq. metres. per 4 Litres.  Maintenance  Misse Well before use. Decking Cleaner can be applied with a watering can, by spray or brush. Leave for 10 mins. then the surface should be scrubbed with a stiff garden brush or broom. Rinse the with clean water using stiff brush, garden hose or power washer.  Coats  One application is usually sufficient.  24 hours depending on temperature and humidity. Do not apply decking coatings to damp timbe as this will affect the adhesion of the coating.  Re-coating Time  N/A  Application Temp.  Ideally 15-25 °C.  Coverage  About 20-24 sq. metres. per 4 Litres.  Maintenance  N/A  Compatibility  Suitable for use on all types of timber and varnished surfaces.  Settlement  SHAKE WELL BEFORE USE.   | Special Features   | Revives the original colour of the wood on faded decks  |
| Application Leave for 10 mins. then the surface should be scrubbed with a stiff garden brush or broom. Rinse the with clean water using stiff brush, garden hose or power washer.  Coats One application is usually sufficient.  24 hours depending on temperature and humidity. Do not apply decking coatings to damp timbe as this will affect the adhesion of the coating.  Re-coating Time N/A  Application Temp. Ideally 15-25 °C.  Coverage About 20-24 sq. metres. per 4 Litres.  Maintenance N/A  Compatibility Suitable for use on all types of timber and varnished surfaces.  Settlement SHAKE WELL BEFORE USE.   | Preparation        | Remove the loose dirt, grease, mildew and mould using a stiff garden brush.   |
| Drying Time  24 hours depending on temperature and humidity. Do not apply decking coatings to damp timber as this will affect the adhesion of the coating.  Re-coating Time  N/A  Application Temp. Ideally 15-25 °C.  Coverage About 20-24 sq. metres. per 4 Litres.  Maintenance  N/A  Compatibility Suitable for use on all types of timber and varnished surfaces.  Settlement SHAKE WELL BEFORE USE.  | Application        | Leave for 10 mins. then the surface should be scrubbed with a stiff garden brush or broom.  |
| Application Temp. Ideally 15-25 °C.  Coverage About 20-24 sq. metres. per 4 Litres.  Maintenance N/A  Compatibility Suitable for use on all types of timber and varnished surfaces.  Settlement SHAKE WELL BEFORE USE.   | Coats              | One application is usually sufficient.  |
| Application Temp. Ideally 15-25 °C.  Coverage About 20-24 sq. metres. per 4 Litres.  Maintenance N/A  Compatibility Suitable for use on all types of timber and varnished surfaces.  Settlement SHAKE WELL BEFORE USE.   | Drying Time        | 24 hours depending on temperature and humidity. Do not apply decking coatings to damp timber as this will affect the adhesion of the coating.   |
| Coverage About 20-24 sq. metres. per 4 Litres.  Maintenance N/A  Compatibility Suitable for use on all types of timber and varnished surfaces.  Settlement SHAKE WELL BEFORE USE.  | Re-coating Time    | N/A   |
| Maintenance N/A  Compatibility Suitable for use on all types of timber and varnished surfaces.  Settlement SHAKE WELL BEFORE USE.  | Application Temp.  | Ideally 15-25 °C.   |
| Compatibility Suitable for use on all types of timber and varnished surfaces.  Settlement SHAKE WELL BEFORE USE.   | Coverage           | About 20-24 sq. metres. per 4 Litres.   |
| Settlement SHAKE WELL BEFORE USE.  | Maintenance        | N/A   |
|  | Compatibility      | Suitable for use on all types of timber and varnished surfaces.   |
| Shelf-life/Storage Many years if stored in original, tightly closed container in normal cool, dry conditions.  | Settlement         | SHAKE WELL BEFORE USE.  |
| Cital mojoration ago in the second control of the second control o | Shelf-life/Storage | Many years if stored in original, tightly closed container in normal cool, dry conditions.  |
| Hazards  Keep reach out of children. Avoid contact with eyes and skin. A full Health & Safety Data Sheet available on request or at <a href="https://www.rustins.co.uk">www.rustins.co.uk</a>  | Hazards            | Keep reach out of children. Avoid contact with eyes and skin. A full Health & Safety Data Sheet is available on request or at <a href="https://www.rustins.co.uk">www.rustins.co.uk</a> |
| Clean-Up Clean equipment in water.   | Clean-Up           | Clean equipment in water.   |
| Sizes 4 L.   | Sizes              | 4 L.  |