

Rustins Ltd, Waterloo Road, London NW2 7TX. Tel: +44 (0)20 8450 4666 [www.rustins.co.uk](http://www.rustins.co.uk)Arsh Build Tech, Unit No-2, Gali No-4, Chauhan Colony, Haryana-121003 | +91-9958502276 | [www.arshbuildtech.com](http://www.arshbuildtech.com)

February 2018

**PRODUCT DATA SHEET**

<b>Product</b>	<b>Quick Dry Decking Stain &amp; Seal</b>
<b>Type</b>	Coloured water-based acrylic stains, Gives long lasting protection to all external wood, while allowing the natural grain to show through. Available in Brown Cedar, Antique Pine, English Oak
<b>Intended Use</b>	Protection of timber decking.
<b>Special Features</b>	Low odour, non-yellowing, resists cracking, peeling, blistering. Wash brushes in water.
<b>Preparation</b>	Surfaces must be clean, dry and free of wax, grease and contaminants, smooth and sound. Fill large cracks, open joints and damaged areas with <b>Rustins Professional Wood Filler</b> . Remove mould, lichens, algae & moss with a stiff garden brush or a scraper. <b>Rustins Decking Cleaner</b> can be use for cleaning. <b>Do not apply to damp timber as this will prevent the product from penetrating the timber and adhering causing the product to flake off.</b>
<b>Application</b>	Using a synthetic brush, apply liberally with a full brush. The first coat may be diluted with water on hot days (up to 15%). Do not apply to hot surfaces or in strong sunlight if possible. Subsequent coats will darken the colour. Do not apply when rain is expected.
<b>Coats</b>	2 coats, but for best protection apply 3 coats.
<b>Drying Time</b>	Touch dry 30 minutes. (On hot days may be touch dry within 10 minutes).
<b>Re-coating Time</b>	4 hours minimum, depending on temperature & humidity.
<b>Application Temp.</b>	Ideally 15-25°C. Do not apply below 10°C, in high humidity or if rain is expected.
<b>Coverage</b>	12-15 sq. metres per litre, per coat, depending on absorbency of surface.
<b>Maintenance</b>	Clean surface thoroughly with <b>Rustins Decking Cleaner</b> and apply further coats as required.
<b>Compatibility</b>	May be applied over old existing coatings if these are in good condition. If applying over wood preservatives test on a small area to ensure the varnish dries and adheres well.
<b>Settlement</b>	<b>STIR WELL BEFORE USE</b>
<b>Shelf-life/Storage</b>	Many years if stored in original, tightly closed container in normal conditions. Do not store below 5°C. <b>PROTECT FROM FROST.</b>
<b>Hazards</b>	Non-flammable. Avoid contact with eyes, skin and clothes. Keep out of reach of children. A full Safety Data Sheet is available upon request or on <a href="http://www.rustins.co.uk">www.rustins.co.uk</a>
<b>Clean-Up</b>	With water whilst still wet. If dried-on, clean equipment & brushes with <b>Rustin's Brush Restorer</b> .
<b>Sizes</b>	2.5 L