

Rustins Ltd, Waterloo Road, London NW2 7TX. Tel: +44 (0)20 8450 4666 www.rustins.co.uk

Arsh Build Tech, Unit No-2, Gali No-4, Chauhan Colony, Haryana-121003 | +91-9958502276 | www.arshbuildtech.com

October 2020

PRODUCT DATA SHEET

PRODUCT DATA SHEET
Quick Dry Outdoor Woodstain
Coloured water-based acrylic varnish, available in Gloss or Satin. Gives long lasting protection to all external wood, allowing the natural grain to show through.
Exterior joinery both hard & softwood, doors, windows, garden furniture, conservatories. May also be used as a sealer for concrete. NOTE: use Rustins Quick Dry Decking Oil on timber decking.
Low odour, resists cracking, peeling, blistering. Wash brushes in water. Available in Light, Medium or Dark Oak, Mahogany, Teak, Walnut and Ebony
Surfaces must be clean, dry and free of wax, grease and contaminants, smooth and sound. Fill large cracks, open joints and damaged areas with a high quality flexible filler. Wash oily woods, knots or resinous areas with white spirit. Remove mould, lichens, algae & moss with brush, scraper & domestic bleach, then rinse thoroughly and allow to dry. <b>Rustins Wood Dye</b> may be applied to bare wood prior to varnishing.
Using a synthetic brush, apply liberally with a full brush finishing with the grain. The first coat may be diluted with water on hot days (up to 15%). Do not apply to hot surfaces or in strong sunlight if possible or if rain is likely.
Apply 3 coats and lightly sand after 1st coat if there is raising of the grain.
Touch dry 30 minutes. (On hot days may be touch dry within 10 minutes).
4 hours minimum, depending on temperature & humidity.
Ideally 15-25°C. Do not apply below 10°C, or in high humidity or if rain expected.
12-15 sq. metres per litre per coat, depending on absorbency of surface.
Re-coat every 2 to 3 years. Clean with a mild detergent solution and lightly sand to provide key.
May be applied over old existing coating if these are in good condition and rubbed down to provide a key. Coatings not in good condition should be removed with <b>Rustins Strypit Paint and Varnish Stripper</b> . If applying over wood preservatives test on a small area to ensure the varnish dries and adheres well.
STIR WELL BEFORE USE. May dry glossy if not adequately stirred.
Many years if stored in original, tightly closed container in normal conditions. <b>PROTECT FROM FROST.</b>
Non-flammable. Avoid contact with eyes, skin and clothes. A full Safety Data Sheet is available upon request or on <u>www.rustins.co.uk</u>
With water whilst still wet. If dried-on, clean equipment & brushes with Rustins Brush Restorer.
250ml 500ml 1 L 2.5 L